CDR1 Model Number Builder

DVB-T COFDM Video/Audio Receiver

Frequency Band	
U1 = UHF Band	340.0-399.9 MHz
L1 = Lower L-band	1435-1535 MHz
L2 = Upper L-band	1700-1850 MHz
S1 = S-band	2200-2399 MHz
S2 = ISM S-band	2400-2499 MHz
S3 = Full S-Band	2200-2499 MHz
C1 = Lower C-Band	4400-4900 MHz
C2 = Upper C-Band	4900-4999 MHz
C3 = Full C-Band	4400-4999 MHz
ZZ = Custom	Specify

Bandwidth
D = 6/7/8 MHz DVB-T
N = 2.5 MHz Narrowband and DVB-T
U = 1.25 MHz Ultra-Narrowband, Narrowband, and DVB-T

Signal Strength Indication
C = LCD Meter
E = LED Bar
X = None

Frequency
(Fixed Frequency Only)
Enter the Frequency in MHz (0000.00M format)
or
Custom Options
Consult factory for available options

Series

Chassis Finish
G = Gold Iridite
N = Nickel Plated

Communication Interface
R = RS-232
T = TTL (3.3V)
2 = RS-422 (Differential)
8 = RS-485 (Differential)

Frequency Selection
C = Channelized (Local/Remote)
R = Remote Only

Decryption
1 = ABS 16-Bit
2 = AES 256-Bit

Default Video Standard
N = NTSC
P = PAL

Audio
X = None
S = Stereo Audio

Data Interface
D = RS-232/TTL (3.3V)
2 = RS-422 (Differential)
8 = RS-485 (Differential)

Notes:

Advanced Microwave Products
8748 Technology Way
Reno, NV 89521

Phone: (775) 345-9933
Fax: (775) 345-9913
E-mail: sales@advmw.com
Web: www.advmw.com