

CNR1 Model Number Builder

Narrowband COFDM Video/Audio Receiver

Frequency Band	
U1 = UHF Band	340.0-399.9 MHz
L1 = Lower L-band	1435-1535 MHz
L2 = Upper L-band	1700-1850 MHz
S1 = S-band	2200-2399 MHz
S2 = ISM S-band	2400-2499 MHz
S3 = Full S-Band	2200-2499 MHz
ZZ = Custom	Specify

Signal Strength Indication

- C = LCD Meter
- E = LED Bar
- X = None

Bandwidth

N = 2.5 MHz Narrowband

Frequency


(Fixed Frequency Only)

Enter the Frequency in MHz
(0000.00M format)

or

Custom Options

Consult factory for available options



Series

- ### Chassis Finish
- G = Gold Iridite
 - N = Nickel Plated

Communication Interface

- R = RS-232
- T = TTL (3.3V)
- 2 = RS-422 (Differential)
- 8 = RS-485 (Differential)

Frequency Selection

- C = Channelized (Local/Remote)
- R = Remote Only

Compression

- J = JPEG2000

Data Interface

- D = RS-232/TTL (3.3V)
- 2 = RS-422 (Differential)
- 8 = RS-485 (Differential)

Audio

- X = None
- S = Stereo Audio

Default Video Standard

- N = NTSC
- P = PAL

Notes:



Advanced Microwave Products
8748 Technology Way
Reno, NV 89521

Phone: (775) 345-9933
Fax: (775) 345-9913
E-mail: sales@advmw.com
Web: www.advmw.com